

Engine List - Doosan

Genset Model	Prime power/ Standby power		Engine model	Fuel consumption L/h	Cylinder	Displacement (L)	Genset Dimension (mm)	Weight (kg)
	KVA	KW						
GHPD66	60/66	48/53	DB58	13.9	6L	5.8	2700x1050x1570	1100
GHPD96	88/96	70/77	D1146	20.6	6L	8.1	2700x1050x1570	1500
GHPD138	125/138	100/110	D1146T	25.9	6L	8.1	2700x1050x1570	1600
GHPD186	169/186	135/150	P086TI-1	43.1	6L	8.1	2900x1100x1719	1750
GHPD220	200/224	160/166	P086TI	43.1	6L	8.1	2900x1100x1719	1825
GHPD303	275/303	220/242	P126TI	58.1	6L	11.1	3200x1150x1820	2200
GHPD343	312/343	250/275	P126TI-II	60.0	6L	11.1	3200x1150x1820	2300
GHPD412	375/412	300/330	P158LE-1	89.3	8V	14.6	3300x1500x1970	2500
GHPD440	400/440	320/352	P158LE	89.3	8V	14.6	3300x1550x2100	2800
GHPD500	450/500	360/400	P158LE-S	99.5	8V	14.6	3500x1550x2100	3000
GHPD500-I	450/500	360/400	P158FE	105.1	8V	14.6	3500x1550x2100	3000
GHPD550-I	500/550	400/440	P180LE	111.6	10V	18.3	3250x1550x2160	3200
GHPD550-II	500/550	400/440	P180LE-S	108.9	10V	18.3	3250x1550x2160	3200
GHPD550-III	500/550	400/440	P180FE	115.2	10V	18.3	3250x1550x2160	3200
GHPD633	575/633	460/506	P222LE-1	120.6	12V	21.9	3500x1550x2200	3600
GHPD660	600/660	480/528	P222LE	134.0	12V	21.9	3550x1550x2200	3600
GHPD688-I	625/688	500/550	P222LE	134.0	12V	21.9	3530x1550x2200	3700
GHPD688-II	625/688	500/550	P222LE-S	130.0	12V	21.9	3530x1550x2200	3800
GHPD715-I	650/715	520/572	P222LE-S	130.0	12V	21.9	3600x1550x2200	3800
GHPD715-II	650/715	520/572	P222FE	151.0	12V	21.9	3800x1550x2200	3900
GHPD750	----/750	----/600	P222LE-II	162.6	12V	21.9	3800x1550x2200	3900